## CLASSIC 6" SIDE ZIP

- Slip and oil resistant quiet rubber outsole; exceeds ASTM F489-96 test standards
- Electrical Hazard Protection; meets ASTM F2412-11 & F2413-11 EH test standards
- Stitched toe and heel for durability and increased service life
- Custom molded phylon midsole for lightweight comfort and cradled support
- Texon<sup>®</sup> stability platform insole for lateral support and torsional stability; with steel shank to accomodate proper flex point to help reduce fatigue
- Full grain polishable toe for improved durability and comfort

- 1000 Denier Nylon Upper for increased strength and durability

1251 • 1251W

- Custom molded thermoplastic heel counter and toe box to provide that already "broken in" out of the box fit and additional lateral support
- Foam padding in tongue and collar protection and increased breathability
- Removable custom fit EVA orthotic for all day comfort, also treated with AEGIS<sup>®</sup>
- Moisture wicking lining treated with AEGIS® anti microbial
- Durable brass alloy, rust proof hardware
- PU collar for easy cleaning
- Triple stitched upper with 3 ply bonded nylon thread for extended durability
- Custom YKK<sup>®</sup> zipper and housing with Velcro<sup>®</sup> closure for easy on and off fit








🍐 Aegis Anti-Microbial Lining

REINAL S.W.A.T.



Electrical Hazard Protection

1251	Regular Width (D) 4-11.5, 12, 13, 14, 15, 16 EU (D) 39 - 45, 46, 47, 48.5, 50	38 oz. (1090 gm)/pr Size 9 / 42
1251W	Wide Width (EEE) 7-11.5, 12, 13, 14, 15, 16 EU (EEE) 39 - 45, 46, 47, 48.5, 50	38 oz. (1090 gm)/pr Size 9 / 42

1821 Industrial Drive Stockton, CA 95206 Tab. (200) 224 4200 - Faur (200) 224 4250 - Faurilli in

Tel: (209) 234-4200 Fax: (209) 234-4250 Email: info@originalswat.com

BLACK